

# REVESORB-FT30-VG1

## REVESORB-FT30 faced with a lightweight vinyl Coated glass cloth

**PRODUCT FORMAT:** Sheet material.

**PRODUCT FORMAT:** Sheets 2440 x 1220 x thickness.  
Thickness from 6 to 100 mm.

**PROPERTIES:**

**Facing**

Base fabric – Fibreglass

Weight – 190g/m<sup>2</sup>

Colour – Silver Grey or Black

Resistant to Oil, grease or petrol.

Hydrolysis resistance allows washing with soap Solution.

**FIRE RATING:**

**BS4735:** 1971 – Self Extinguishing

FMVSS302 – Self-Extinguishing.

BS476 Part 7 – Class 1.

EPI Radiateur – M1.

**Working Temperature range:** -6°C to +120°C

**Foam**

See **REVESORB FT30**

Some reduction in acoustic absorption at high frequencies is an inevitable consequence of providing a tougher facing.

**USAGE:**

High resilience acoustic lining. Preferred for industrial enclosures in food and process industries where durability and hygiene are necessary.

**PRODUCT OPTIONS:**

**REVESORB-FT30-VG1-DS1** as above but with self adhesive damping sheet.

**REVESORB FT30-AD3** as above but with self Adhesive backing.

REF: C141093g PIFT30VG1